



# OCULARIS™ PLUG OWNERS MANUAL

Do NOT attempt to use the Ocularis™ Banding System without first reading and understanding this simple manual.




## THE FOUR RULES OF OCULARIS.™



**1 Flatbands:** Plugs on shooter side. Bands pull around the frame.

**2 Tubes:** Plugs on target side. Bands pull through the frame.



**3 Heavy tubes:** White plugs only.

**4 All bands:** use the ball bearing.



**NEVER** pull tubes around the frame.  
**NEVER** pull flatbands through the frame.



## INSTALLATION INSTRUCTIONS

Ball bearings may be inserted prior to or after band installation. Rubbing alcohol or saliva may be used to lubricate the bearing for easier insertion.

### Flatbands:

Place the band into the fork from the 'target' side of the slingshot in whichever orientation you desire - over the top, through the forks, or



SHOOTER SIDE

somewhere in between. Push the plug securely into place from the 'shooter' side of the slingshot while gently pulling the band towards the 'target' side of the slingshot to ensure the plug is completely seated against the slingshot fork.

### Tubes:

Insert the looped tubular band from the 'shooter' side of the slingshot as shown. Place the Ocularis™ Plug on the 'target' side of the slingshot and seat the tubular bands in the saddles on plug as shown. Take care to ensure the plug is placed in the center point of the loop prior to inserting plug from 'target' side of slingshot. Push in plug while gently pulling looped bands from the 'shooter' side of the slingshot.



TARGET SIDE

Repeat the process for the second forktip. Double check that both bands are installed in the same orientation. Carefully test the assembly to ensure it is secure before firing the slingshot.

